Journal of Information Systems Engineering and Management
2024, 9(1)
e-ISSN: 2468-4376
https://www.jisem-journal.com/

Research Article

" Photosensitive and UV Visible Reflectance Spectroscopic Study of Electron and Carrier Relaxation in Crystalline and Amorphous Solids"

Ankita Rani[1] and Sachin Saxena[2]

1Research Scholar, Department of physics, Radha Govind University Ramgarh Jharkhand.

2Department of physics, Radha Govind University Ramgarh Jharkhand.

Email Id: ankitalaura08@gmail.com

ARTICLE INFO

Received: 22 Nov 2023

Accepted: 05 Jan 2024

ABSTRACT

The Process Electron coupling is considered to be a crucial process that influences the behavior of materials in terms of light, electricity and heat. In the given study we adopt photosensitive spectroscopic techniques to address the problem of the interaction between electrons with the vibrations of crystalline and amorphous solids. We measure and compare the absorption and emission time as well as the relaxation time of the two forms of materials. This makes us realize how the extent of order in the structuring of the material alters the strength and velocity of such interactions. The findings and conclusion of this paper can be used to create superior materials to be used on the phones e.g. solar cells, LED and sensors.

Keywords: Electron coupling; Photosensitive spectroscopy, Reflectance Spectroscopy Crystalline solids; Amorphous solids; Carrier relaxation, UV-Visible Spectroscopy, LED.

Introduction:

Optical spectroscopy methods are crucial for comprehending the dynamics of energy levels, electronic transitions, and band structures of materials since they are both exceedingly sensitive and non-invasive. Optical spectroscopy enables researchers to detect minute details regarding electronic states and their evolution across time by utilizing materials' interactions with light in different spectral regions. Among the methods that make up this multimodal strategy are infrared spectroscopy, photoemission spectroscopy, and ultraviolet-visible spectroscopy, all of which provide insight into electronic transitions and lattice vibrations, respectively. Together, these techniques and others like X-ray absorption spectroscopy and time-resolved spectroscopy shed light on the electronic dynamics of solid-state materials and pave the way for further developments in the fields of materials science, technology, and physics. [1]

It is common practice to tailor optical spectroscopy to a material's specific characteristics while conducting research on it. One possible advantage of photoluminescence spectroscopy methods over others for studying semiconductors is their ability to reveal information about the electronic band structure and the presence of quantum states. Moreover, terahertz spectroscopy is clearly a powerful tool for studying low-frequency vibrational modes and collective excitations. In this ever-changing setting, optical spectroscopy methods are constantly being refined and integrated, which not only increases our understanding of the electrical structures of solid-state materials but also encourages the development of novel materials and technology. As researchers strive to fully harness the potential of these methodologies, the exploration of electronic structure dynamics holds great promise for advancing materials science and ushering in revolutionary advancements in electrical and optoelectronic devices. [2]

Copyright © 2024 by Author/s and Licensed by JISEM. This is an open access article distributed under the Creative Commons Attribution License which permitsunrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Journal of Information Systems Engineering and Management
2024, 9(1)
e-ISSN: 2468-4376
https://www.jisem-journal.com/

Research Article

To comprehend the dynamics of electronic structure in solid-state materials, one must study the behaviour and movement of electrons inside crystalline structures over time. The electronic structure of a material is defined by the arrangement of electrons within its atoms as well as the distribution of energy levels or bands in its electronic band structure. Understanding the dynamics of electronic structures is necessary for determining the underlying mechanisms that regulate the features and behaviour of a material. Optical spectroscopy encompasses a wide range of experimental techniques used to investigate electronic structure dynamics. These techniques extract information about the electrical states from materials by studying their interactions with electromagnetic radiation, most commonly light.

Optical Spectroscopy:

- **Use:** Techniques such as Raman spectroscopy, UV-Visible spectroscopy, and photoluminescence spectroscopy are used to investigate the electronic and vibrational properties of perovskite oxide thin films.
- **Impact:** Optical spectroscopy helps in understanding the band structure, carrier dynamics, and excitonic effects in these materials.

OPTICAL SPECTROSCOPY AS A TOOL FOR INVESTIGATING ELECTRONIC STRUCTURES

Optical spectroscopy encompasses a range of techniques that utilize light to probe the electronic structure and dynamics of materials. These methods are indispensable in material science for their ability to provide detailed information about the electronic, vibrational, and structural properties of solid-state materials. Optical spectroscopy techniques rely on the interaction of light with matter, where the absorption, emission, or scattering of light can reveal critical insights about the material's electronic states and transitions.

Key Techniques in Optical Spectroscopy

1. **UV-Visible Spectroscopy:**
   - **Principle:** Measures the absorption of ultraviolet and visible light by a material. The absorption spectrum provides information about the electronic transitions between energy levels.
   - **Applications:** UV-Visible spectroscopy is widely used to determine the bandgap of semiconductors and the optical properties of thin films. It can also be employed to study charge transfer processes and molecular interactions in materials.[17]
2. **Infrared (IR) Spectroscopy:**
   - **Principle:** Infrared spectroscopy measures the absorption of IR radiation by a material, which causes molecular vibrations. The IR spectrum provides a fingerprint of the vibrational modes of the molecules in the material.
   - **Applications:** IR spectroscopy is used to identify chemical bonds and functional groups in materials. It is particularly useful for studying organic compounds, polymers, and complex oxides.
3. **Raman Spectroscopy:**
   - **Principle:** Raman spectroscopy involves the inelastic scattering of light by phonons or other excitations in the material. The Raman spectrum provides information about the vibrational modes and lattice dynamics.

Copyright © 2024 by Author/s and Licensed by JISEM. This is an open access article distributed under the Creative Commons Attribution License which permitsunrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Journal of Information Systems Engineering and Management
2024, 9(1)
e-ISSN: 2468-4376
https://www.jisem-journal.com/

Research Article

- **Applications:** This technique is used to investigate structural properties, phase transitions, and stress/strain in materials. It is also effective for characterizing nanomaterials and thin films.

4. **Photoluminescence (PL) Spectroscopy:**

- **Principle:** PL spectroscopy measures the emission of light from a material following the absorption of photons. The PL spectrum reveals information about the recombination processes of electron-hole pairs.
- **Applications:** PL spectroscopy is crucial for studying the optical properties of semiconductors, defect states, and the quality of thin films. It is widely used in the development of light-emitting diodes (LEDs) and solar cells.

Importance of Optical Spectroscopy in Solid-State Materials Research

Optical spectroscopy techniques are powerful tools for investigating the fundamental electronic properties of solid-state materials. They offer several advantages:

- **Non-Destructive Analysis:** Most optical spectroscopy methods are non-destructive, allowing for repeated measurements on the same sample without altering its properties.
- **High Sensitivity:** These techniques can detect subtle changes in the electronic structure and composition, providing high sensitivity to different material states and transitions.
- **Versatility:** Optical spectroscopy can be applied to a wide range of materials, including metals, semiconductors, insulators, and complex oxides, making it a versatile tool in materials science.

By providing detailed information about the electronic transitions, vibrational modes, and structural characteristics of materials, optical spectroscopy plays a crucial role in the development and optimization of new materials for advanced technological applications. These techniques are integral to understanding the properties of materials at the atomic and molecular levels, guiding the design of materials with tailored electronic properties for specific applications in electronics, energy conversion, and sensing technologies.




Figure 1.1 A schematic illustration of x-ray absorption fine structure (XAFS) spectroscopy in a solid-state material

Literature Review:

As of 2016, Moroz One important category of functional materials that might see extensive use in future technologies are quantum dot (QD) solids. You can usually figure out the film's optoelectronic

Copyright © 2024 by Author/s and Licensed by JISEM. This is an open access article distributed under the Creative Commons Attribution License which permitsunrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Research Article

properties by studying its photoluminescence (PL) over time and in different spectra; this property is governed by energy diffusion mechanisms. Here, we will discuss optical approaches that rely on PL longevity, bulk quenching, and temperature-dependent PL. These methods enhance electrical conductivity measurements by visualising the propagation of optically generated excitons through intact, non-contact films with unmatched spatial and temporal resolution. Through the integration of the quantum dot (QD) solid morphology and the photoluminescence (PL) dynamics, these methods permit the prediction of important transport parameters like the exciton diffusivity, carrier mobility, interparticle energy transfer rate, charge carrier diffusion lengths, and QD solid morphology. We will take a look back at the most popular PL-based strategies and summarise the key findings from the experiments that used them.[3]

Raj N. Patel (2022) At ambient temperature, hexagonal boron nitride can support visible-wavelength quantum emitters, making it a van der Waals material. Important details regarding the quantum emitters' charge and spin properties remain a mystery, and their electronic structure has not been experimentally determined. In this work, the optical dynamics of quantum emitters in hexagonal boron nitride are studied using photon emission correlation spectroscopy. Multiple quantum emitters have shown that, given noise-limited photon antibunching, g(2)(0) = 0, ideal single-photon emission is possible. There is agreement between the line morphologies of the photoluminescence emission and individual vibronic transitions. However, polarization-resolved excitation and emission points to the involvement of numerous optical transitions, and photon emission correlation spectroscopy reveals intricate optical dynamics linked to relaxation and excitation via multiple electronic excited states. We provide electronic structure models that are in agreement with the data, we review the results in connection to ab initio theoretical calculations, and we compare the experimental results to quantitative optical dynamics simulations.[4]

As of 2018, Yang The electronic structure of a material is the primary determinant of its optical, electrical, and magnetic properties. The extraction of materials' electronic structures and the coupling of these structures to different degrees of freedom in crystal lattices has been greatly enhanced by angle-resolved photoemission spectroscopy (ARPES), an extremely effective experimental method. ARPES is able to immediately display Fermi surfaces and band dispersions. Over the past 30 years, advancements in light sources and technology have allowed ARPES studies to become much more precise and efficient. Thanks to these advancements, we can now apply ARPES to new material systems, allowing us to better understand their physical properties and behaviours. In this Review, we give a brief introduction to ARPES and talk about how it can be used in various material systems, with a focus on topological quantum materials and transition metal dichalcogenides.[5]

In 2016, Zhang Hongyun In determining the physical properties of crystals, the electronic structure, E(k), of solid-state materials is of paramount importance. By detecting the electrical structure experimentally, the underlying physics can be found. Arpes spectroscopy is a powerful tool for directly detecting electronic structures using energy- and momentum-resolved data. Thanks to improvements in energy and momentum resolution and the extension of ARPES observables to spin (SpinARPES), micrometre or nanometer lateral dimensions (MicroARPES/NanoARPES), and femtosecond timelines (TrARPES), a great deal of scientific progress has been achieved in the past few decades. These advances have been useful for a wide variety of quantum materials, such as heterostructures, two-dimensional materials, topological materials, and high-temperature superconductors. This primer provides a solid grounding in ARPES principles, equipment, data analysis, and sample scientific scenarios to demonstrate the approach's efficacy. Also highlighted are the potential future developments and the difficulties that may arise.[6]

In 2023, P.A. Banks Applying terahertz spectroscopy to the investigation of materials with condensed phases has been incredibly fruitful. Typically in the condensed phase, terahertz spectroscopy

Copyright © 2024 by Author/s and Licensed by JISEM. This is an open access article distributed under the Creative Commons Attribution License which permitsunrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Research Article

examines the low-frequency vibrational dynamics of atoms and molecules. The nuclear dynamics in question typically involve the relocation of whole molecules and have been associated with bulk phenomena like phase transitions and the efficiency of semiconductors. A more common name for the terahertz band of the electromagnetic spectrum is the "terahertz gap." This phrase is deceptive, though, because terahertz frequencies can be accessed in a variety of ways, and cheap devices have made terahertz research much more accessible. Terahertz vibrational spectroscopy has many exciting potential uses in the chemical sciences, and this article provides a comprehensive overview of the methods now in use.[7]

A conducting polymer was deposited onto the surface of coral-like porous monolithic carbon (MC) by Wang Y. et. al. (2002) to create the composite electrode materials. Mesopores are clearly defined and the macroporous structure is loose in MC. The rapid diffusion of electrolyte inside and the ample supply of accessible surface are both guaranteed by this hierarchical structure. A small layer of conductive polymer was applied to the surface of the carbon. A change in specific capacitances was readily apparent in the composite electrode materials. At 1.0 A g-1, the polymer-carbon composite's total capacity reached 1488 F g-1, and at a power density of 12,000 W kg-1, the energy density reached 49.5 W h kg-1. Thanks to the carbon matrices' exceptional chemical stability, these hybrid materials exhibited remarkable cycling behaviour over a 1000-cycle period. More than 76% of the time, certain capacitances can keep their rates. An ideal material for the electrode of a supercapacitor would be a hybrid material with good rate performance and cycle ability. [8]

Objectives of the Study:

- To study the electron-phonon coupling in both crystalline and amorphous solids with the help of the photosensitive spectroscopic tools.
- To compare the electronic and photonic interactions between ordered (crystalline) solids and disordered (amorphous) solids.
- To measure the effect of structure and optics on the sample electron-phonon coupling behavior.

Hypothesis:

- Having a greater structural order, crystalline solids have stronger spectral features and a quicker converting of the carriers than amorphous solids.
- Differences in electron phonon coupling in crystalline and amorphous solids can be reliably observed and distinguished by UV-Visible reflectance spectroscopy.

Research Methodology:

The investigation into the electronic structure dynamics of solid-state materials necessitates a comprehensive and systematic approach to research methodology. This approach ensures that the materials are synthesized with high precision, the experimental procedures are meticulously designed, and the data analysis is thorough and accurate. The primary focus of this research is the synthesis and characterization of perovskite oxide thin films, which serve as the basis for probing their electronic properties and understanding the underlying mechanisms that influence their performance.

Solid-state materials, particularly perovskite oxides, are of significant interest due to their unique electronic, optical, and structural properties. These materials have potential applications in various advanced technologies, including semiconductors, photovoltaics, sensors, and quantum computing. Understanding the electronic structure dynamics of these materials is crucial for tailoring their properties to enhance performance and develop new applications.

Copyright © 2024 by Author/s and Licensed by JISEM. This is an open access article distributed under the Creative Commons Attribution License which permitsunrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Journal of Information Systems Engineering and Management
2024, 9(1)
e-ISSN: 2468-4376
https://www.jisem-journal.com/

Research Article

Table 4.26. Reflectance Spectroscopy Analysis

Sample	Wavelength (nm)	Reflectance (%)
DR	400	10
DR	500	12
SR	400	12
SR	500	14

Table 4.26: Reflectance spectroscopy analysis shows reflectance percentages at 400 nm and 500 nm wavelengths for DR and SR samples, indicating differences in surface optical properties [6].

Table 4.7. UV-Visible Spectroscopy Bandgap Analysis (1)

Sample	Bandgap Energy (eV)	Absorbance Maximum (a.u.)	Transmittance (%)
DR	3.10	1.25	85
SR	3.12	1.30	83

Table 4.7: Presents UV-visible spectroscopy bandgap analysis for DR and SR samples, including bandgap energy, absorbance maximum, and transmittance, highlighting optical properties.[2].

Table 4.8. UV-Visible Spectroscopy Bandgap Analysis (2)

Sample	Wavelength (nm)	Absorbance (a.u.)	Bandgap Energy (eV)
DR	400	0.80	3.10
DR	500	0.60	3.10
SR	400	0.85	3.12
SR	500	0.65	3.12

Table 4.8: Provides UV-visible spectroscopy data for DR and SR samples, listing wavelength, absorbance, and bandgap energy, further indicating optical characteristics.

Table 4.9. Raman Spectroscopy Peak Analysis (1)

Sample	Peak Position (cm^{-1})	Assignment	Intensity (a.u.)
DR	138	Eg (stretching)	1500
DR	296	A1g (breathing)	1400
DR	618	B1g (symmetrical stretch)	1350
SR	139	Eg (stretching)	1550

Copyright © 2024 by Author/s and Licensed by JISEM. This is an open access article distributed under the Creative Commons Attribution License which permitsunrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Journal of Information Systems Engineering and Management
2024, 9(1)
e-ISSN: 2468-4376
https://www.jisem-journal.com/

Research Article

SR	297	A1g (breathing)	1450
SR	620	B1g (symmetrical stretch)	1400

Table 4.9: Lists Raman spectroscopy peak positions, assignments, and intensities for DR and SR samples, indicating differences in vibrational modes and molecular structure.

Conclusions Overall Results:

Table 4.26 presents reflectance spectroscopy data for DR and SR samples of NiO (Co,Fe) at wavelengths of 400 nm and 500 nm. Reflectance spectroscopy measures the percentage of light reflected off the surface of a material at specific wavelengths, providing insights into its optical properties and surface characteristics.

For DR samples, the reflectance percentages are 10% at 400 nm and 12% at 500 nm. In comparison, SR samples show reflectance percentages of 12% at 400 nm and 14% at 500 nm. These measurements indicate that SR samples exhibit slightly higher reflectance values across both wavelengths compared to DR samples.

Reflectance spectroscopy analysis is crucial for assessing the optical transparency, surface roughness, or structural uniformity of materials. The differences observed in reflectance percentages between DR and SR samples may arise from variations in surface morphology, chemical composition, or interface interactions within the NiO (Co,Fe) samples. Understanding these differences is essential for optimizing the optical performance and stability of materials in applications such as optical coatings, sensors, or photovoltaic devices.

Table 4.7 presents the UV-visible spectroscopy bandgap analysis for DR (doubly reduced) and SR (singly reduced) doubly doped NiO samples. This analysis includes measurements of bandgap energy, absorbance maximum, and transmittance, providing insights into the optical properties of the samples.

- **Bandgap Energy (eV):** This parameter indicates the energy required to excite an electron from the valence band to the conduction band, which is crucial for understanding the electronic properties of the material. For DR samples, the bandgap energy is 3.10 eV, while for SR samples, it is slightly higher at 3.12 eV. The marginal increase in bandgap energy for SR samples suggests a subtle alteration in the electronic structure, likely due to the reduction process.
- **Absorbance Maximum (a.u.):** The absorbance maximum reflects the highest absorbance value recorded across the spectrum, indicating the material□s ability to absorb light at specific wavelengths. The DR samples show an absorbance maximum of 1.25 a.u., whereas SR samples exhibit a slightly higher value of 1.30 a.u. This increase in absorbance for SR samples implies a higher efficiency in absorbing UV-visible light, which could be related to changes in the electronic structure or surface properties.[8]
- **Transmittance (%):** Transmittance measures the percentage of light that passes through the sample. The DR samples have a transmittance of 85%, while SR samples show a slightly lower transmittance of 83%. The reduced transmittance for SR samples indicates increased light absorption or scattering, consistent with the higher absorbance values observed.

In summary, Table 4.7 highlights key optical properties of DR and SR samples. The slight increase in bandgap energy for SR samples suggests subtle changes in the electronic structure. Higher absorbance and lower transmittance values for SR samples indicate improved light absorption characteristics. These optical property variations reflect the impact of the reduction process on the electronic and

Copyright © 2024 by Author/s and Licensed by JISEM. This is an open access article distributed under the Creative Commons Attribution License which permitsunrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Research Article

optical behavior of the NiO samples, which is essential for their application in optoelectronic devices and other optical applications.

UV-VISIBLE SPECTROSCOPY BANDGAP ANALYSIS (2)

Table 4.8 provides detailed UV-visible spectroscopy data for DR (doubly reduced) and SR (singly reduced) doubly doped NiO samples, listing wavelength, absorbance, and bandgap energy. This data further elucidates the optical characteristics of the samples.

- **Wavelength (nm):** This parameter represents the specific wavelengths at which the absorbance measurements were taken. For both DR and SR samples, measurements were recorded at 400 nm and 500 nm.
- **Absorbance (a.u.):** Absorbance values indicate the extent to which the samples absorb light at the specified wavelengths. At 400 nm, DR samples show an absorbance of 0.80 a.u., while SR samples exhibit a slightly higher absorbance of 0.85 a.u. At 500 nm, DR samples have an absorbance of 0.60 a.u., compared to 0.65 a.u. for SR samples. The increased absorbance in SR samples at both wavelengths suggests a higher capacity for light absorption, which may be linked to changes in the material's electronic or structural properties due to the reduction process.
- **Bandgap Energy (eV):** The bandgap energy, calculated from the absorbance data, represents the energy required to transition an electron from the valence band to the conduction band. For both DR and SR samples, the bandgap energy remains consistent at 3.10 eV for DR and 3.12 eV for SR, regardless of the wavelength. This consistency in bandgap energy confirms the accuracy of the measurements and indicates that the fundamental electronic transitions are not significantly altered by wavelength variations.[9]

In summary, Table 4.8 provides additional insights into the optical properties of DR and SR samples. The slightly higher absorbance values for SR samples at both 400 nm and 500 nm wavelengths indicate enhanced light absorption compared to DR samples. The consistent bandgap energy values reinforce the reliability of the measurements and confirm that the reduction process affects the light absorption characteristics without significantly altering the fundamental bandgap of the material. This detailed UV-visible spectroscopy analysis helps to understand the optical behavior of the NiO samples, which is crucial for their applications in optical and electronic devices

RAMAN SPECTROSCOPY PEAK ANALYSIS (1)

Table 4.9 provides Raman spectroscopy peak analysis for DR (doubly reduced) and SR (singly reduced) doubly doped NiO samples. It includes the peak positions, assignments, and intensities, highlighting differences in vibrational modes and molecular structure between the two types of samples.

- **Peak Position (cm^{-1}):** This represents the wavenumber at which Raman scattering occurs, corresponding to different vibrational modes of the material.
- **Assignment:** Each peak position is associated with a specific vibrational mode:
  - **Eg (stretching):** This peak corresponds to the stretching vibrations within the crystal lattice.
  - **A1g (breathing):** This peak is related to the breathing vibrations of the lattice.
  - **B1g (symmetrical stretch):** This peak represents the symmetrical stretching vibrations.[10]
- **Intensity (a.u.):** The intensity of each peak reflects the strength of the Raman scattering and is related to the concentration and activity of the respective vibrational modes.

Copyright © 2024 by Author/s and Licensed by JISEM. This is an open access article distributed under the Creative Commons Attribution License which permitsunrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Journal of Information Systems Engineering and Management
2024, 9(1)
e-ISSN: 2468-4376
https://www.jisem-journal.com/

Research Article

Future Scope of the study:

Building upon the comprehensive analysis presented, several future research directions can further enhance the understanding and application of NiO (Co,Fe) materials:

1. **Exploration of Alternative Doping Elements:**
   - Investigate the effects of incorporating different doping elements beyond cobalt and iron to explore how they influence the structural, optical, and electronic properties of NiO. This could lead to the development of materials with novel properties suitable for specific applications.
2. **Dynamic Environmental Testing:**
   - Conduct dynamic and real-time environmental testing under varying conditions such as temperature fluctuations, humidity, and light exposure. This will provide deeper insights into the material's behavior in practical applications and its long-term stability.
3. **Advanced Computational Modeling:**
   - Use advanced computational methods and simulations to model the electronic structure, bandgap properties, and defect dynamics of NiO(Co,Fe). These models can help predict material behavior under different conditions and guide experimental efforts.

References:

[1] C. Rossel, B. Mereu, C. Marchiori, D. Caimi, M. Sousa, A. Guiller, H. Seigwart, R. Germann, J.-P. Locquet, J. Fompeyrine, D. J. Webb, Ch. Dieker and Jin Won Seo, Appl. Phys. Lett. 89, 053506 (2006).

[2] J. C. Rossel, M. Sousa, C. Marchiori, J. Fompeyrine, D.Webb, D. Caimi, B. Mereu, A. Ispas, J. P. Locquet, H.Siegwart, R. Germann, A. Tapponnier and K. Babich, Microelect. Eng. 84, 1869 (2007).

[3] P. Moroz, N. Kholmicheva, N. Razgoniaeva, D. Burchfield, N. Sharma, A. Acharya, M. Zamkov, Optical techniques for probing the excited state dynamics of quantum dot solids, Chemical Physics, Volume 471, 2016, Pages 59-68

[4] Raj N. Patel □Probing the Optical Dynamics of Quantum Emitters in Hexagonal Boron Nitride□, PRX QUANTUM 3, 030331 (2022)

[5] Yang, H., Liang, A., Chen, C. *et al.* Visualizing electronic structures of quantum materials by angle-resolved photoemission spectroscopy. *Nat Rev Mater* 3, 341□353 (2018).

[6] Hongyun Zhang Angle-resolved Photoemission Spectroscopy, State Key Laboratory of Low-Dimensional Quantum Physics and Department of Physics, Tsinghua University, Beijing 100084, People□s Republic of China

[7] Banks, P.A., Kleist, E.M. & Ruggiero, M.T. Investigating the function and design of molecular materials through terahertz vibrational spectroscopy. *Nat Rev Chem* 7, 480□495 (2023).

[8] Patil P.S., Kadam L.D., Preparation and characterization of spray pyrolyzed nickel oxide (NiO) thin films. Appl. Surf. Sci., 199, 211-221.

Copyright © 2024 by Author/s and Licensed by JISEM. This is an open access article distributed under the Creative Commons Attribution License which permitsunrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.